

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction products

Thermal insulation product for buildings – In-situ formed loose-fill mineral wool (MW) product

for use as thermal insulation product for buildings subject to regulations on reaction to fire, with specification and performance as specified on page 2 in this certificate.

Product names: ISOVER InsulSafe® and ISOVER InsulSafe® Wall

placed on the market under the name or trademark of

Saint-Gobain Sweden AB

Box 212
SE-191 23 Sollentuna, Sweden

and produced in the manufacturing plant

Saint-Gobain Sweden AB, ISOVER, Storgatan 29, SE-267 82 Billesholm, Sweden

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard

EN 14064-1:2010

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2011-11-28 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Issued by notified body 0402

The validity of this certificate can be verified on our website.

Martin Tillander
Director Product Certification

Certificate 0402-CPR-SC1317-11 | issue 4 | 2021-01-31

RISE Research Institutes of Sweden AB | Certification

Box 857, SE-50115 Borås, Sweden

+46 10 516 50 00 | certifiering@ri.se | www.ri.se

2P06721

This document is the property of RISE and may not be reproduced other than in full, except with the prior written approval by RISE

Specification

In-situ formed loose-fill made of glass wool with organic additive content 2 % or less.

Range of density:

ISOVER InsulSafe® 15–35 kg/m³

ISOVER InsulSafe® Wall 26–30 kg/m³

Designation code according to manufacturer:

MW-SS EN 14064–1-S1-MU1

MW-SS EN 14064–1-S1-WS-MU1

Performance

Reaction to fire (class): A1