



Certificate of constancy of performance

0402 - CPR – SC1317-11

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Thermal insulation product for buildings – In-situ formed loose-fill mineral wool (MW) product as specified in appendix to this certificate.

Product name: ISOVER Insulsafe®

placed on the market under the name or trademark of

Saint-Gobain Sweden AB

**ISOVER
SE-267 82 BILLESOLM
Sweden**

and produced in the manufacturing plant

Saint-Gobain Sweden AB, ISOVER Storgatan 29, SE-267 82 BILLESOLM, Sweden

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard

EN 14064-1:2010

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2011-11-28 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

2016-04-19

**SP Technical Research Institute of Sweden
Certification, Notified Body No. 0402**

Johan Åkesson
Product Certification Manager

Magnus Sturesson
Certification officer



Certificate of constancy of performance

0402 - CPR – SC1317-11 appendix

Thermal insulation product for buildings – In-situ formed loose-fill mineral wool (MW) product, *ISOVER Insulsafe*®

Thermal insulation product for use subjected to regulations on reaction to fire.
In-situ formed loose-fill made of glass wool.

Specifications:

| | |
|--|--|
| Applicable density for installation (kg/m³): | Designation code according to manufacturer: |
| 15-18 | MW-SS EN 14064-1-S2-MU1 |
| 21-30 | MW-SS EN 14064-1-S1-MU1 |

Performance/Classification:

Reaction to fire (class): A1