

Sektionsfaktorer med isolertjocklekar för HEB profiler

Kritisk ståltemperatur = 450 °C												
Profil	HEB		R 30		R 60		R 90		R 120		R 180	
	F/A-4 m ⁻¹	F/A-3 m ⁻¹	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm
HE100B	154	115	20	20	30	20	80	50		80		
HE120B	141	106	20	20	25	20	60	40		80		
HE140B	130	98	20	20	20	20	50	40	80	60		
HE160B	118	89	20	20	20	20	50	40	80	60		
HE180B	110	83	20	20	20	20	40	30	80	60		
HE200B	102	77	20	20	20	20	40	30	80	50		
HE220B	97	73	20	20	20	20	40	30	60	50		
HE240B	91	68	20	20	20	20	40	25	60	40		80
HE260B	88	66	20	20	20	20	30	25	60	40		80
HE280B	85	64	20	20	20	20	30	25	60	40		80
HE300B	80	60	20	20	20	20	30	20	50	30		60
HE320B	77	58	20	20	20	20	30	20	50	30		60
HE340B	75	57	20	20	20	20	30	20	50	30		60
HE360B	73	56	20	20	20	20	30	20	50	30		60
HE400B	71	56	20	20	20	20	30	20	50	30		60
HE450B	69	55	20	20	20	20	25	20	40	30	80	60
HE500B	67	54	20	20	20	20	25	20	40	30	80	60
HE550B	67	55	20	20	20	20	25	20	40	30	80	60
HE600B	67	56	20	20	20	20	25	20	40	30	80	60
HE650B	66	56	20	20	20	20	25	20	40	30	80	60

3-sidig brandpåverkan, ej översida (F/A-3)

4-sidig brandpåverkan (F/A-4)