

Sektionsfaktorer med isolertjocklekar för HEM profiler

Kritisk ståltemperatur = 450 °C												
HEM		R 30		R 60		R 90		R 120		R 180		
Profil	F/A-4 m ⁻¹	F/A-3 m ⁻¹	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm	F/A-4 mm	F/A-3 mm
HE100M	85	65	20	20	20	20	30	25	60	40	100	80
HE120M	80	61	20	20	20	20	30	25	50	40	100	80
HE140M	76	58	20	20	20	20	30	20	50	30	100	60
HE160M	71	54	20	20	20	20	30	20	50	30	100	60
HE180M	68	52	20	20	20	20	25	20	40	30	80	60
HE200M	65	49	20	20	20	20	25	20	40	25	80	50
HE220M	62	47	20	20	20	20	25	20	40	25	80	50
HE240M	52	39	20	20	20	20	25	20	30	25	60	50
HE260M	51	39	20	20	20	20	20	20	30	20	60	50
HE280M	50	38	20	20	20	20	20	20	25	20	50	50
HE300M	43	33	20	20	20	20	20	20	20	20	50	50
HE320M	43	33	20	20	20	20	20	20	20	20	50	50
HE340M	43	34	20	20	20	20	20	20	20	20	50	50
HE360M	44	34	20	20	20	20	20	20	20	20	50	50
HE400M	45	36	20	20	20	20	20	20	20	20	50	50
HE450M	47	38	20	20	20	20	20	20	25	20	50	50
HE500M	48	39	20	20	20	20	20	20	25	20	50	50
HE550M	50	41	20	20	20	20	20	20	25	20	50	50
HE600M	51	42	20	20	20	20	20	20	30	20	60	50
HE650M	52	44	20	20	20	20	20	20	30	20	60	50

3-sidig brandpåverkan, ej översida (F/A-3)

4-sidig brandpåverkan (F/A-4)